

You need fresh air, so does your home.





## Greentek Peace of Mind

All Greentek products are backed by the best limited warranty in the industry, for your peace of mind.

You benefit from a lifetime warranty on the core, a 10-year warranty on our ventilation motors and a 5-year warranty on all other components. So you can breathe easy.





## Heat Recovery Ventilator ENERGY STAR® Rated PH Series (PH 7.15 ES and PH 10.22 ES)





## Features & Benefits



DuoTrol balancing system

Silent and economical... By reducing motor speed to balance the unit, you avoid the noise that would be produced

by balancing dampers. In addition, with this technology the unit will consume less energy.



SPM attachment system

The entire line of Greentek HRV/ERV products is designed for installation by a single person. "Single Person Mounting" will enable you

to save time and effort by offering you a variable attachment system.



**ISF** 6" (diam.) collar system

Quick and simple to install thanks to our revolutionary "Insert Slide and Fix" collar system. The "ISF" 6" (diam.)

collar system enables you to manipulate duct within your reach and then insert by sliding it in place, for a better and quicker installation.



Range of controls For optimal performance of your HRV/ERV system.

The entire range of controls is offered with features making your ventilation system simple,

easy to operate and backed by a 5-year limited warranty. Choose from: RD-1,

RD-2, RD-3P, RD-4P, EHC1.0TC, EHC1.5DC and T-3 (Push-Button Timer)




High-Performance motors

All Greentek products are designed with high-performance and reliable motors for your comfort and peace of mind. Factory sealed and dynamically

balanced, our motors are maintenance-free for years to come.

Ventilation Performance PH 7.15 ES								
External Static		Net Supply		Gross A	Gross Air Flow		Gross Air Flow	
Pres	ssure	Air Flow		Sup	Supply		Exhaust	
Pa	in. wg	L/s	CFM	L/s	CFM	L/s	CFM	
25	0.1	71	150	72	153	80	170	
50	0.2	64	136	65	138	73	155	
75	0.3	58	123	58	123	66	140	
100	0.4	52	110	52	110	59	125	
125	0.5	47	100	47	100	52	110	
150	0.6	40	85	41	87	47	100	
175	0.7	33	70	33	70	40	85	
HVI	quidelines set by Natural Resources Canada and the US EPA. It meets							



Vent	tilation	Perfo	rman	ce PH	10.22	2 ES	
	External Static Pressure		Net Supply Air Flow		Gross Air Flow Supply		ir Flow aust
Pa	in. wg	L/s	CFM	L/s			CFM
25	0.1	111	235	112	237	120	254
50	0.2	102	216	103	218	111	235
75	0.3	93	197	94	199	102	216
100	0.4	85	180	86	182	92	195
125	0.5	78	165	79	167	83	176
150	0.6	70	148	71	150	75	159
175	0.7	62	131	63	133	66	140
HVI	quidelines set by Natural Resources Canada and the US EPA. It meets						

		-	Supply	<b>-</b> □-E	chaust				
	300								
$cfm (L/s = n \times 0.4719)$	250	-							Н
9.0	200	-							Н
×	150				,	7			
II	150							7	
Ë	100	-							Н
μ	50								
U	30								
	٥l	_		2 0	2 0				ب
		0.	1 0.	.2 0	.3 0.	4 0	.5 0.	.6 0	./
	External Static Pressure in wg (Pa = $n \times 248.36$ )								

Er	ner	gy	Perf	PH 7	'.15 ES		
		oply erature	N Air F	et Flow	Power Consumed	Sensible Recovery Efficiency	Adjusted Sensible Recovery Efficiency
	°C	°F	L/s	CFM	Watts	SRE %	ASRE %
5	0	32	30	64	52	70	76
HEATING	0	32	40	85	64	65	71
₹	0	32	50	106	78	64	69
罜	-25	-13	33	70	51	60	62

Er	ner	ду	Perf	PH 10	).22 ES		
	Supply Temperature		N Air F	et Flow	Power Consumed	Sensible Recovery Efficiency	Adjusted Sensible Recovery Efficiency
	°C	°F	L/s	CFM	Watts	SRE %	ASRE %
5	0	32	31	66	58	75	82
HEATING	0	32	43	91	70	73	80
I≅	0	32	60	127	88	69	75
Ξ	-25	-13	31	66	55	60	63

SPECIFICATIONS	PH 7.15 ES	PH 10.22 ES
Size	23%" x 21½" x 11%"	23%" x 21½" x 16½"
Weight	50 lbs (22.68 Kg)	65 lbs (29.48 Kg)
CFM	30 to 150	50 to 220
Type of heat exchanger	Cross-flow (Polypropylene)	Cross-flow (Polypropylene)
Exchange surface	104 ft <sup>2</sup>	150 ft <sup>2</sup>
Voltage	120 VAC @ 60 Hz	120 VAC @ 60 Hz
Amperage	1.0 A	1.5 A
Defrost type	Evacuation	Evacuation
Certification	HVI, <sub>c</sub> CSA <sub>us</sub>	HVI, cCSA <sub>us</sub>
Rated	ENERGY STAR®	ENERGY STAR®
	21½" 6"	211/2"



## Greentek

50 Kanalflakt Way, Bouctouche, NB Canada E4S 3M5

Toll free: 1 888 724-5211 Fax: 1 (866) 426-7430 Visit us at: www.greentek.ca

You can find Greentek Indoor Air Quality products at the following distributor:









Greentek reserves the right to modify a product, without prior notice, whether in design, colour or specifications, in order to offer at all times a quality product that is highly competitive. Please consult your national and local building codes to find out whether the installation of electrical products requires the services of a certified technician or electrician. Greentek™ is a registered Trademark used under license by Systemair Inc. All rights reserved.